


# Medallion with beads in rings off chains

Photos, diagrams and text © 2024 Jennifer Williams

## Requirements:

Size 20 thread, 2 shuttles, 6 six size 3mm beads, a fine crochet hook and the usual tatting equipment.

## Special abbreviations:


CTM = continuous thread method   
 SH. = shuttle, R. = ring, p = picot. cl = close ring,  
 RW = reverse work, DNRW = do not reverse work,  
 SS = swap shuttles, CH. = Chain, + = join,  
 RoCH = ring off chain




Wind two shuttles CTM with about 4½ metres on shuttle 1 and 2 metres on shuttle 2 and ½ metre in between (7 metres altogether)

SH,1 R.A 8, p, 6, p, 2, cl  
 R.B 2, + to ring A, 6, p, 2, p, 2, p, 6, p, 2, cl  
 R.C 2, + to ring B, 6, p, 8, cl, (Fig 1) RW

**Fig 1**




**Fig 2**




CH. (Fig 2) 6, SS, DNRW  
 SH,2 RoCH D Add one of the beads to the centre of this ring ( see technique sheet) 4, p, 4, p, 4, cl, SS DNRW  
 SH,1 CH, 6, tension the chain to curve as in the sample above, RW

**Fig 3**



**Fig 4**




\*R.E (Fig 3) 8, + to the last ring of the previous three ring group, 6, p, 2, cl  
 R,F 2, + to previous ring, 6, p, 2, p, 2, p, 6, p, 2, cl  
 R.G 2, + to previous ring, 6, p, 8, cl, RW  
 CH. (Fig 4) 6, SS. DNRW  
 SH,2 RoCH H Add one of the beads to the centre of this ring as before.  
 4, + to previous RoCH, 4, p, 4, cl, SS, DNRW  
 SH,1 CH. 6, tension to curve as in the sample above, RW,\*\*

Repeat from \* to \*\* three more times then continue

- SH.1 R.U 8, + tp ring S, 6, p, 2, cl  
 R.V 2, + to ring U, 6, 2, p, 2, p, 2, p, 6, p, 2, cl  
 R.W 2, + to ring V, 6, + to ring A, 8, cl, RW  
 CH. 6, SS, DNRW
- SH.2 RoCH X Add a bead to the centre of this ring as before.  
 4, + to RoCH.T, 4, + to RoCH. D, 4, cl, SS, DNRW
- SH.1 CH. 6, tension as before

Cut and tie to the base of rings A, B and C then secure the ends.




## Adding a bead to the centre of a ring - method 2

Jennifer Williams March 2011


1/

Thread the bead onto a loop in the shuttle thread that will be used to work the ring. Secure in place using a safety pin. Take the shuttle thread round your hand and back below the bead, as in the diagram below.




2/

Work the ring as far as the join  
Take your shuttle to the left out of the way




3/

Remove the safety pin carefully and, using a fine crochet hook, pull a loop from the thread round your hand through the small pin hole.




4/

Pick up the shuttle again and pass it through the loop from the back to the front



5/

Adjust the threads making sure that the core (shuttle) thread is not pulled back through the safety pin hole



6/

Work the required number of stitches to complete the ring then pull the core (shuttle) thread to close the ring in the usual way.

